



Test Report: NPB-450-12

450W High Reliable Ultra Wide Output Range
Intelligent Battery Charger

■ DESIGN VERIFY TEST

Output Function Test
Input Function Test
Protection Function Test
Control Function Test
Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test
E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST



■ DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	BOOST CHARGE VOLTAGE (default)	14.4V± 0.24 V	I/P: 230 VAC O/P:BAT. LOAD Ta:25°C	14.41 V
2	FLOAT CHARGE VOLTAGE (default)	13.8V± 0.12 V	I/P: 230 VAC O/P:BAT. LOAD Ta:25°C	13.82V
3	MAX. OUTPUT CURRENT	25A± 0.25 A	I/P: 230 VAC O/P:C.V =13.4V Ta:25°C	24.97A
4	MAX. POWER	420W	I/P: 230 VAC O/P:C.V =16.8V Ta:25°C	420.9W
5	LEAKAGE CURRENT FROM BATTERY (TYP)	<1mA	I/P: AC OFF O/P:BAT. LOAD Ta:25°C	77.µA
6	OUTPUT CURRENT RANGE	50%~100%Io	I/P: 230 VAC O/P:C.V =16.8V Ta:25°C	11.72~24.81A


INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	90VAC~264VAC 127VDC~370VDC	(1) I/P:TESTING O/P:FULL LOAD (2) I/P:DC TESTING(L:+ N:-) O/P: FULL LOAD (3) I/P:DC TESTING(L:- N:+) O/P: FULL LOAD Ta:25°C	(1) 86.6V~264V (2)120 Vdc~370Vdc/FULL LOAD (3) 120Vdc~370Vdc/FULL LOAD
			I/P: LOW-LINE-3V=87 V HIGH-LINE+15%= 300 V O/P:BAT. LOAD (PLEASE CHECK DERATING CURVE) ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST: OK
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE	I/P: 90 VAC ~264 VAC O/P:FULL~MIN LOAD Ta:25°C	TEST: OK
3	LEAKAGE CURRENT	< 0.75 mA / 240VAC	I/P: 240 VAC O/P:Min LOAD Ta:25°C	0.47 mA
4	INPUT CURRENT (TYP)	230 V/ 2.2 A 115 V/ 4.5A	I/P: 230 VAC I/P: 115 VAC	I =2.00A/ 230VAC I =4.09A/ 115VAC



450W High Reliable Ultra Wide Output Range
Intelligent Battery Charger

NPB-450 series

			O/P:BAT. LOAD Ta:25°C	
5	POWER FACTOR (TYP)	0.95/ 230 VAC 0.98/ 115 VAC	I/P: 230 VAC I/P: 115 VAC O/P:BAT. LOAD Ta:25°C	PF= 0.989/ 230VAC PF= 0.997/ 115VAC
6	EFFICIENCY (TYP)	92%	I/P: 230 VAC O/P:BAT. LOAD(C.V =16.8V) Ta:25°C	92.1%
7	INRUSH CURRENT (TYP)	230 V/ 50 A COLD START	I/P: 230 VAC O/P:BAT. LOAD Ta:25°C	I =49A/ 230VAC T50= 1.024ms/230V
<p>INPUT=230VAC/50HZ @ FULL LOAD CH2 : AC Input Voltage CH4 : Input current (1V=1A)</p> 				
8	GAIN-PHASE MARGIN TEST	GAIN MARGIN < -10dB PHASE MARGIN > =60 Gain Curve slope: -10dB/dec~-40dB/dec	(1) CC MODE(Vboost)/ 90% LOAD /264Vac (2) CC MODE(Vboost)/ 90% LOAD /90Vac Ta:25°C	(1) 69.2439 °/ -21.276 dB / -27.8 dB/dec (2) 70.4614 °/ -21.326 dB / -32.7 dB/dec

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER VOLTAGE PROTECTION	CH1:21.5V~26V PROTECTION RESULT Shut down and latch off o/p voltage, re-power on to recover.	I/P: 264 VAC I/P: 90 VAC O/P:TESTING Ta:25°C	25.4V/ 264VAC 25.4V/ 90VAC ROTECTION TYPE : Shut down and latch off o/p voltage, re-power on to recover.
2	OVER TEMPERATURE PROTECTION	SPEC: NO DAMAGE Shut down o/p voltage, recover automatically after temperature goes on.	I/P: 264 VAC I/P: 90 VAC O/P:BAT. LOAD	O.T.P. Active PROTECTION TYPE : OK Shut down o/p voltage, recover automatically after temperature goes down.
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE 22.5A~30A Constant current	I/P: 264 VAC O/P: BAT. LOAD Ta:25°C	NO DAMAGE <u>25.02 A</u> PROTECTION TYPE : Constant current



450W High Reliable Ultra Wide Output Range
Intelligent Battery Charger

NPB-450 series

		limiting ,charger will shut down after 5 sec, re-power on to recover.		limiting ,charger will shut down after 5 sec, re-power on to recover.
4	BATTERY REVERSE POLARITY	Protected internal reverse detection, No damage, re-power on to recover after conduction is removed.	I/P: 230 VAC O/P:BAT. LOAD Ta:25°C	Protected internal reverse detection, No damage, re-power on to recover after conduction is removed
5	ERROR INPUT HIGH VOLTAGE BATTERY	Shut down o/p voltage, re-power on to recover	I/P: 230 VAC O/P:BAT. LOAD Ta:25°C	PROTECTION TYPE : Shut down o/p voltage, re-power on to recover

CONTROL FUNCTION TEST

N O	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT												
1	FAN SPEED CONTROL	FAN control mosfet duty: 30% (-1%) @RTH5<45°C FAN control mosfet duty : 100% (-1%) @RTH5>60°C	I/P: 230 VAC O/P:BAT. LOAD Ta:25°C	<u>29.6%</u> @RTH5<45°C <u>99.6%</u> @RTH5>60°C												
2	REMOTE CONTROL	Rc+ / Rc- OPEN/(-0.5~0.5V): Charger stop charging SHORT/(10.8~13.2V) : Charger normal work	I/P: 230 VAC O/P:BAT. LOAD Ta:25°C	TEST: <u>OPEN/-0.5~2.5 V</u> <u>SHORT/ 2.7~ 13.2V</u> (1) Remote off Pin= <u>4.08W</u> (2) Remote off Vo= <u>0.04V</u>												
3	AUX POWER	OUTPUT VOLTAGE RANGE : 10.8~13.2V OUTPUT RIPPLE&NOISE: 150mVp-p	I/P: 230 VAC O/P:BAT. LOAD Ta:25°C	TEST: <u>12.04</u> V <u>33</u> mVp-p												
4	LED INDICATOR	<table border="1"> <thead> <tr> <th>LED</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Green</td> <td>Float(stage 3) or Battery full</td> </tr> <tr> <td>Orange</td> <td>Charging (stage 1 or stage 2)</td> </tr> <tr> <td>Orange (Flashing)</td> <td>Auto sensing for charging</td> </tr> <tr> <td>Red</td> <td>Abnormal status (OTP,OVP, Short, Reverse polarity, Charging timeout.)</td> </tr> <tr> <td>Red (Flashing)</td> <td>The LED will flash with the red light when the internal temperature reaches 95°C; under this condition, the unit still operates normally without entering OTP.</td> </tr> </tbody> </table>	LED	Description	Green	Float(stage 3) or Battery full	Orange	Charging (stage 1 or stage 2)	Orange (Flashing)	Auto sensing for charging	Red	Abnormal status (OTP,OVP, Short, Reverse polarity, Charging timeout.)	Red (Flashing)	The LED will flash with the red light when the internal temperature reaches 95°C; under this condition, the unit still operates normally without entering OTP.	I/P: TESTING VAC O/P:TESTING LOAD Ta:25°C	TEST : <u>OK</u>
LED	Description															
Green	Float(stage 3) or Battery full															
Orange	Charging (stage 1 or stage 2)															
Orange (Flashing)	Auto sensing for charging															
Red	Abnormal status (OTP,OVP, Short, Reverse polarity, Charging timeout.)															
Red (Flashing)	The LED will flash with the red light when the internal temperature reaches 95°C; under this condition, the unit still operates normally without entering OTP.															



450W High Reliable Ultra Wide Output Range
Intelligent Battery Charger

NPB-450 series

5	TEMPERATURE COMPENSATION	I/P: 230 VAC O/P:BAT. LOAD Ta:25°C			
		Constant Voltage			
		SPEC:	Ta=0°C (17K Ω)	Ta=25°C (5K Ω)	Ta=50°C (1.7K Ω)
		TEST RESULT:	14.85±0.24V	14.4±0.24V	14.13±0.24V
6	CHARGE OK	The TTL signal out, Charger OK = 4.5 ~ 5.5V; Charger failure or protection = -0.5 ~ 0.5V	I/P: 230 VAC O/P:BAT. LOAD Ta:25°C	TEST: Charger OK = <u>5.18</u> V; Charger failure= <u>34</u> mV; Charger protection= <u>34m</u> V	
7	BATTERY FULL SIGNAL	The TTL signal out, Battery full = 4.5 ~ 5.5V ; Charging = -0.5 ~ 0.5V	I/P: 230 VAC O/P:BAT. LOAD Ta:25°C	TEST: Battery full = <u>5.1</u> V Charging = <u>33m</u> V	

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q 5/Q6 Rated : 600V/25 A	AC ON/OFF I/P:High-Line +3V = 267 V VDS : O/P: (1)CV(max) =20V (2) CV(min) =10.5V (3)no load (4)OUTPUT SHORT Ta:25°C	Q5 VDS : (1) 492V (2) 472V (3) 480V (4) 480V Q6 VDS : (1) 476V (2) 444V (3) 456V (4) 484V
2	P.F.C Transistor (D to S) or (C to E) Peak Voltage	Q 1 Rate: 600V /18 A	AC ON/OFF I/P:High-Line +3V = 267 V VDS : O/P: (1)CV(max) =20V (2) CV(min) =10.5V (3)no load (4)OUTPUT SHORT Ta:25°C	VDS : (1) 508V (2) 464V (3) 496V (4) 452V
3	AUX MOS	U600 Rate: 725V/ 0.88A	AC ON/OFF I/P:High-Line +3V = 267 V VDS : O/P: (1)CV(max) =20V (2) CV(min) =10.5V (3)no load (4)OUTPUT SHORT Ta:25°C	VDS : (1) 621V (2) 577V (3) 613V (4) 585V
4	P.F.C DIODE	D19 Rated : 650 V/ 6 A	AC ON/OFF I/P:High-Line +3V = 267 V O/P: (1)CV(max) =20V (2) CV(min) =10.5V (3)no load (4)OUTPUT SHORT Ta:25°C	(1) 464V (2) 416V (3) 460V (4) 464V



5	Diode Peak Voltage	Q211/ Q213 Rated :60V/ 120A -	AC ON/OFF I/P:High-Line +3V = 267 V VDS : O/P: (1)CV(max) =20.5V (2) CV(min) =10.5V (3)no load (4)OUTPUT SHORT Ta:25°C	Q211 VDS : (1) 48.5V (2) 36.1V (3) 46.5V (4) 48.9V	Q213 VDS : (1) 49.3V (2) 42.9V (3) 48.5V (4) 49.3V
6	Input Capacitor Voltage	C 5 Rated : 220u / 450 V	AC ON/OFF I/P:High-Line +3V = 267 V VDS : O/P: (1)CV(max) =20V (2) CV(min) =10.5V (3)no load (4)OUTPUT SHORT Ta:25°C	(1) 447V (2) 437V (3) 445V (4) 447V	
7	Control IC Voltage Test	PWM IC U3Rated 8.9V~15.5V PFC IC U2Rated 11V~26V O/P IC U801 Rated 4.5V~36V U100 Rated 6.5V~35V MCU IC U701 Rated 2.4V~ 3.6 V	AC ON/OFF I/P:High-Line +3V = 267 V VDS : O/P: (1)CV(max) =20V (2) CV(min) =10.5V (3)no load (4)OUTPUT SHORT Ta:25°C	U3 (1) 14.0V (2) 14.0V (3) 14.2V (4) 13.6V U2 (1) 14.6V (2) 14.4V (3) 14.6V (4) 14.0V U801 (1) 10.67V (2) 10.67V (3) 10.67V (4) 10.67V	U100 (1) 12.60V (2) 12.60V (3) 12.68V (4) 13.08V U701 (1) 3.32V (2) 3.32V (3) 3.32V (4) 3.32V

■ SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	I/P-O/P: 3 KVAC/min I/P-FG:2 KVAC/min O/P-FG:0.5KVAC/min	I/P-O/P: 3.6 KVAC/min I/P-FG: 2.4 KVAC/min O/P-FG: 0.6 KVAC/min Ta:25°C	I/P-O/P: 2.468 mA I/P-FG: 3.297 mA O/P-FG: 0.971 mA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 600 VDC I/P-FG: 600 VDC O/P-FG: 600 VDC Ta:25°C	I/P-O/P: 9999MΩ I/P-FG: 7698MΩ O/P-FG :9999MΩ NO DAMAGE
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40A / 2min Ta:25°C	17mΩ



E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	HARMONIC	BS EN/EN61000-3-2 CLASS A	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	PASS
2	CONDUCTION	BS EN/EN 55032 (CISPR32), BS EN / EN55014-1 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL/50% LOAD Ta:25°C	PASS Test by certified Lab
3	RADIATION	BS EN/EN 55032 (CISPR32), BS EN / EN55014-1 CLASS B	I/P:230VAC/50HZ O/P:FULL /50%LOAD Ta:25°C	PASS Test by certified Lab
4	E.S.D	BS EN/EN61000-4-2 AIR : 8KV / Contact : 4KV	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A
5	E.F.T	BS EN/EN61000-4-4 INPUT: 1KV	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A
6	SURGE	BS EN/EN 61000-4-5 L-N :1KV L,N-PE:2KV	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A
7	Test by certified Lab & Test Report Prepare Any contradictions of the test results, please refer to the latest EMC test report			

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	TEMPERATURE RISE TEST	MODEL : NPB-450-12 1. ROOM AMBIENT BURN-IN : 2 HRS I/P : 230VAC O/P : FULL LOAD Ta= 27.6 °C 2. HIGH AMBIENT BURN-IN : 2 HRS I/P : 230VAC O/P : FULL LOAD Ta= 53.8 °C		



450W High Reliable Ultra Wide Output Range
Intelligent Battery Charger

NPB-450 series

				NO	Position	ROOM AMBIENT Ta= 27.6 °C	HIGH AMBIENT Ta=53.8°C
				1	ZNR1	36.1°C	62.8°C
				2	U3	43.0°C	70.3°C
				3	LF1	38.5°C	65.5°C
				4	RY1	40.3°C	67.2°C
				5	RTH2	40.4°C	67.6°C
				6	LF3	49.9°C	76.4°C
				7	BD1	48.5°C	74.2°C
				8	C8	49.6°C	76.3°C
				9	Q1	50.3°C	76.9°C
				10	TSW1	42.2°C	68.5°C
				11	L1	68.4°C	96.0°C
				12	C5	46.9°C	73.0°C
				13	R18	56.8°C	83.7°C
				14	C24	45.0°C	71.6°C
				15	Q6	45.3°C	71.9°C
				16	C60	52.3°C	76.8°C
				17	T1	66.9°C	90.9°C
				18	T600	47.0°C	74.5°C
				19	Q211	56.2°C	81.9°C
				20	Q213	46.6°C	76.1°C
				21	C112	51.8°C	77.4°C
				22	C115	32.6°C	60.1°C
				23	Q354	45.7°C	80.1°C
				24	U701	31.2°C	60.5°C
				25	LF100	37.8°C	67.2°C
				26	U503	41.4°C	59.6°C
				27	U150	39.4°C	67.7°C
				28	RG5	34.9°C	62.8°C
				29	J102	49.8°C	80.5°C
				30	R228	54.0°C	83.2°C
				31	D19	57.1°C	82.9°C
				32	U2	49.8°C	75.9°C
				33	D651	49.2°C	76.0°C
				34	RG6	38.8°C	67.2°C
				35	Q500	47.0°C	74.9°C
				36	U100	51.2°C	78.4°C
				37	RTH5	52.3°C	78.8°C
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR		I/P : 230VAC/100VAC O/P : 100 %LOAD Ta= -35°C		TEST : OK	
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C NO DAMAGE		I/P : 272 VAC O/P : FULL LOAD Ta= 49 °C HUMIDITY= 95 %R.H		TEST : OK	
4	TEMPERATURE COEFFICIENT	± 0.05%/ (0°C~50°C)		I/P : 230 VAC O/P : FULL LOAD		0.0061 %/°C(0~50°C)	



450W High Reliable Ultra Wide Output Range
Intelligent Battery Charger

NPB-450 series

5	STORAGE TEMPERATURE TEST	-40~85°C	1. Thermal shock Temperature : -45°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10CYCLE 5. Input/Output condition : STATIC
6	THERMAL SHOCK TEST	-30~50°C	1. Thermal shock Temperature : -35°C~ +55°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 16 CYCLE 5. Input/Output condition : 15cycle:230V/ FULL LOAD AC ON 3sec/AC OFF 1sec TEST 1cycle:230V/ FULL LOAD Burn In Test
7	VIBRATION TEST	10 ~ 500Hz, 2G 10min./1cycle, 60min. each along X, Y, Z axes	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 10min/sweep cycle (4) Acceleration : 3G (5) Test Time : 180min in each axis (X.Y.Z) (6) Ta : 25°C
8	CAPACITOR LIFE CYCLE	SUPPOSE C112 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta= 25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta= 50 °C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta= 50 °C LIFE TIME (4) I/P : 230VAC O/P : 50% LOAD Ta= 50 °C LIFE TIME	(1) 745973.3HRS (2) 137470.7HRS (3) 276216.1HRS (4) 451756.4HRS
9	MTBF	Conducted by Parts Stress Analysis Prediction 821.0K hrs min. Telcordia SR-332 (Bellcore) ; 83.4K hrs min. MIL-HDBK-217F (25°C)	
10	Ongoing Reliability Test	I/P : 230VAC O/P : FULL LOAD TA=50°C Demonstration Mean Time Between Failure : 30,000 hours	

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	LIUTT		Wangdz

2020.10.1 TAG-QA-009