



Test Report : SMU01K-05N

1W DC-DC Unregulated Single output Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

■ SAFETY TEST

Safety test

■ RELIABILITY TEST

Environment Test

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-3.0% ~ +3.0 % (Max)	I/P:5.0VDC O/P:FULL LOAD Ta:25°C	-1.51%	P
2	RIPPLE & NOISE	75 mVp-p (Max)	I/P:5.5VDC O/P:FULL LOAD Ta:25°C	11 mV	P
3	LINE REGULATION	-12% ~ +12 %	I/P:4.5VDC~5.5VDC O/P:FULL LOAD Ta:25°C	-11.05% ~ +11.40%	P
4	LOAD REGULATION	-8.0% ~ +8.0%	I/P:5.0VDC O/P:10% LOAD~FULL LOAD Ta:25°C	-3.42% ~ +3.22%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	EFFICIENCY	85%	I/P:5.0VDC O/P:FULL LOAD Ta:25°C	86.01%	P
2	DC CURRENT	379 mA / FULL LOAD 10 mA / NO LOAD	I/P:5.0VDC O/P:NO / FULL LOAD Ta:25°C	346 mA / FULL LOAD 6.3 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	SHORT PROTECTION	CONTINUOUS	I/P:5.5VDC O/P:FULL LOAD Ta:25°C	CONTINUOUS, AUTOMATIC RECOVERY	P
2	CASE TEMPERATURE	+115°C max	I/P:5.0VDC O/P:TESTING Ta: TESTING	OK AUTOMATIC RECOVERY	P

SAFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1500 VDC/min	I/P-O/P:1500 VDC/min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT										
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:5.0VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 4HRS I/P:5.0VDC O/P:FULL LOAD Ta=90°C 3. HIGH AMBIENT BURN-IN : 4HRS I/P:5.0VDC O/P:80% LOAD Ta=105°C												
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> <th>3</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>42.4°C</td> <td>98.8°C</td> <td>111.0°C</td> </tr> </tbody> </table>			NO	Position	1	2	3	1	CASE	42.4°C	98.8°C	111.0°C
NO	Position	1	2	3										
1	CASE	42.4°C	98.8°C	111.0°C										
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 4 HOURS	I/P:5.0VDC O/P: FULL LOAD Ta= -40°C	TEST : OK										

OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT
1	MTBF	MIL-HDBK-217F,GB,25°C TOTAL FAILURE RATE : 0.5 M.T.B.F : 2,000KHRS		

TEST RESULT	TESTER	APPROVAL
PASS	ARCHEN HSIAO	PETER CHENG